



The Fiber Optic Tray KM 4 is designed for up to 24 fibers. It can be used separately mounted on an existing post structure or in conjunction with the [FibeRoad™ System](#). It is compatible with all types of fibers and is very intuitive to use. A full range of Splice Holders is available to ensure compatibility.

- ▶ Capacity of up to 24 splices
- ▶ PLC Splitter capability (small format)
- ▶ [FibeRoad™ System](#) compatible
- ▶ Hinged or stackable mounting
- ▶ No need to measure fibers before splicing
- ▶ Heat shrink splice protector segregation feature
- ▶ Ability to store feeder and drop fibers separately
- ▶ Ability to change direction of the fiber storage
- ▶ Ability to place fibers in a secondary sheath (pigtail, $\varnothing$ 0.9 mm)
- ▶ Suitable for ribbon fibers

**KM 4 (24 splices)**

TECHNICAL SPECIFICATIONS

Flammability Degree	V0
Material	PC / ABS
Color	light gray RAL 7035
Dimensions (H × W × D)	12 × 175 × 149 mm
Weight	0.1 kg

ORDERING CODES

85C3.79/000X	KM 4 Kit for Heat Shrinkable Protection
85C3.82/000X	KM 4 Kit for Crimp Protection
85C3.81/000X	KM 4 Kit for Ribbon Protection
493520	Heat Shrink Splice Protector (compatible with TS 12, 45 × 2.4 mm)



KM 4 (3× ribbon + splitter)



KM 4 (12 splices, fibers in a secondary sheath)



KM 4 (with a lid and sticker)



KM 4 (with a splitter)



KM 4 (FibeRoad™ System – cascade solution)



KM 4 (FibeRoad™ System)



Splice Holder TS 12 (for heat shrink splices)



Splice Holder K 12 (for crimp splices)



Splice Holder RIB 3 (3× ribbon or splitter 4 × 4 mm)

More information: <https://www.micostelcom.com/en/fiber-optic-trays/fiber-optic-tray-km-4>